



The Pearl Medical Series is optimized to meet the demanding requirements of consistent unit-to-unit performance with ease of integration. Standard features include a pilot beam, monitor photodiode and feedback tolerant design.

nLIGHT's proprietary single-emitter integration technology enables industry-leading efficiency and reliability, thus minimizing system footprint and maximizing doctor up-time.

The Pearl uses a revolutionary fiber technology, PowerCore™, which eliminates mode sensitivity to fiber motion, which optimizes consistency of light on skin performance.

## Features

- Patented nXLT™ diode protection for extended life
- Low-current, fault-tolerant architecture
- Industry-leading wall-plug efficiency
- PowerCore™ mode-stable fiber
- Plug and play compatibility with OptoTools™ DL system
- Electrically isolated housing

## Applications

- Acne Treatment
- BPH
- Dental
- Eye Surgery
- Hair Removal
- Leg Vein Treatment
- Surgical

**Proven Performance**

sales@nlight.net • www.nlight.net

## Typical Device Performance

Package		P10					P16				
<b>Optical</b>											
Wavelength	nm	810	980	1470/1530	1700	1908/1940	810	980	1470/1530	1700	1908/1940
Wavelength tolerance	nm	10	10	20	20	20	10	10	20	20	20
CW output power <sup>5</sup>	W	25	30	20	12	8	35	50	35	20	13
Fiber core diameter	µm	400	200/400	200/400	200/400	200/400	400	200/400	200/400	200/400	200/400
Beam divergence	NA <sup>1</sup>	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22
Spectral width (FWHM)	nm	<5	<10	<15	<15	<20	<5	<5	<15	<15	<20
Slope efficiency <sup>5</sup>	W / A	5.5	5.5	4.0	4.0	1.5	8.5	8.5	7.0	6.5	2.5
<b>Electrical</b>											
Power conversion efficiency <sup>5</sup>	%	50	58	35	23	10	50	58	35	23	10
Threshold current	A	1.0	0.4	0.8	1.7	1.1	1.0	0.4	0.8	1.7	1.1
Operating current <sup>5</sup>	A	5.5	6.1	5.7	4.0	7.5	5.0	6.3	6.0	3.1	6.6
Operating voltage	V	9.0	8.3	11.1	8.7	8.8	14.5	13.2	18.5	14.5	14.7
Series resistance	Ω	0.1	0.2	0.3	0.3	0.5	0.2	0.3	0.5	0.5	0.9
Pilot Beam	mW	<1									
<b>Mechanical</b>											
Storage temperature range <sup>2</sup>	°C	-30 to +60									
Mass	gr	100	100	220	220	220	180	180	350	350	350
<b>Thermal</b>											
Thermal resistance <sup>3</sup>	°C / W	0.5	0.8	0.6	0.6	0.8	0.3	0.5	0.3	0.3	0.5
Operating temperature	°C	+15 to +35									
Wavelength temperature coefficient <sup>4</sup>	nm / °C	0.28	0.35	0.55	0.6	0.7	0.28	0.35	0.55	0.6	0.7
<b>Accessories</b>											
PPS™ OEM Diode Driver											
OptoTools™ DL System with DiodeSafe™											
Monitor Photo Diode											

<sup>1</sup> Numerical aperture (NA) is the sine of the half-angle encircling 90% of the optical energy from the fiber.

<sup>2</sup> A non-condensing environment is required for storage and operation.

<sup>3</sup> Thermal resistance is the diode junction temperature shift per incremental Watt of heat load.

<sup>4</sup> The wavelength temperature coefficient is the wavelength shift per °C change at the diode junction.

<sup>5</sup> If Pearl operated with an aiming beam these specification will be altered (consult factory for details)

