



The Summit™ NL-QD-Q1yzz-K package is a conductively cooled diode laser stack (of up to 8 bars) designed to operate at very high temperature. This diode laser bar array benefits from the latest advances in technology. It combines the highest efficiency available today with extremely reliable operation at very high junction temperatures.

The package has been optimized to reduce overall thermal resistance. NL-QD-Q1yzz-K stacks are ideal for applications under severe environmental conditions, such as pumping solid-state lasers in designators and illuminators. This compact and rugged design is well suited to defense and space applications requiring small footprint and high reliability.

---

## Features

- Highest Efficiency
- Highest Temperature Endurance
- Shock and Vibration Rugged
- Tested for Space Applications
- Low Thermal Resistance

---

## Applications

- Target Designation
- Ranging
- LIDAR
- Space Environments
- Multi-Spectral Imaging
- Medical
- Ignition

## Typical Device Performance

Package	NL-QD-Q1yzz-K			
Parameters				
Number of Diode Bars per Stack		zz = 2 to 8		
Pitch between Diode Bars	µm	400		
Emitting Area	mm x mm	(zz – 1)* 0.4		
QCW Output Power per Diode Bar	Watt	60	80	100
Threshold Current	Amp.	19	19	19
Operating Current	Amp.	70	88	105
Operating Current (Maximum)	Amp.	75	97	120
Operating Voltage	Volt	< 2 / Bar		
Total Efficiency	%	48		
Total Efficiency (Minimum)	%	42		
Beam Divergence (FWHM)	Degree	10 x 40		

Variation of wavelength is approximately 0.26 to 0.3 nm/°C.

Standard wavelength is 808nm.

Spectral width is ≤ 4 nm FWHM.

Tolerance on wavelength is +/- 3nm.

Other wavelengths 9xx nm available.

Possibility of pitch between diode bars of 500 µm

Operating at higher power or higher temperature will accelerate component aging, increase threshold current, and decrease slope efficiency.

### CFR Regulation

These components do not comply with the federal regulation (Title 21 CFR, Chapter 1, Subchapter J) as administered by the Center for Device and Radiological Health. Purchaser acknowledges that their products must comply with these regulations before they can be sold to an end-user.



### Notice

nLIGHT continually improves its products to provide our customers with outstanding quality and reliability. nLIGHT may make changes to specifications and product descriptions at any time, without notice. In addition, nLIGHT offers a limited warranty to ensure customer satisfaction. For complete details, please contact your nLIGHT sales representative.

Copyright © 2008 nLIGHT. All rights reserved.

### Package Dimensions

